

SH.038 MAGNUM 6 POINT SALOON 75MM/75MM FIA COMPETITION HARNESS

RMP.10

	<u> </u>										
Date:		Harness Specification Sheet									
Dealer Name:		Customer Notes:									
Customer Name:											
Daytime Contact No:											
Email Address:											
Approval Type:	Qty required:	Colour:									
Make of Vehicle:	Type:	Year:									
Shoulder strap measurements "A" should be taken with driver seated in vehicle with harness fastened tight. Technical Tip: Shoulder measurements "A" under 65cm we recommend a Sewn Bearing Point											
Sewn Bearing Point	Threaded Anchor Point with 3	Shoulder Webbing Width: FHR Specific 50mm 75mm									
Racetoch Standard	Race A 28cm Standard		Length A: cm Measure distance "A" from centre of anchor mounting point to centre of adjuster								
Shoulder Adjuster (Mark appropriate box) Technical Tip: We recommend the aluminium adjuster for fast and easy adjustment											
	l Adjuster 🗌	75mm Aluminium Adjuster 🗌									
Lap Straps - Measurements should be taken with the harness fastened tight and adjustment in midway position. "B" is 65cm as standard from centre of anchor mounting to centre of release buckle. "C" is 12cm as standard from centre of mounting strap to centre of adjuster.											
Pull Up (STD Direction)	B B		Length B: (Overall Length) cm Length C: cm (Adjuster Length)								
Pull Down (Suited for tight cockpits i.e. Kit Car)		Length B: (Overall Length) cm Length C: cm (Adjuster Length)									
Lap Adjuster (Mark appropriate box) Technical Tip: We recommend the aluminium adjuster for fast and easy adjustment											
	Adjuster	75mm Aluminium Adjuster									



SH.038 MAGNUM 6 POINT SALOON 75MM/75MM FIA COMPETITION HARNESS

RMP.10

Rotary Quick Release Buckle Only												
Permanently fixed to Crotch Strap M10-0003 (Standard for a 5pt/6pt Saloon)												
50mm Crutch Straps - Measurements should be taken with the driver seated in the vehicle. 2-point Crutch Moustache "D" is 65cm as standard.												
Pull Down								Length D:	ст			
Sewn Anchorages - Mark appropriate boxes to identify requirements												
Sewn Snap Hook	Sewn 8mm Bolt in Plate	Sewn 9.5mm Bolt in Plate	Sewn 11mm Bolt in Plate	Sewn 13mm Bolt in Plate	Sewn 15mm Bolt in Plate	Sewn Flat Loop 4cm is standard	Sewn Pinched Becket 4cm is standard	Sewn Carabina				
									FHR 50mm Shoulder Straps			
									75mm Shoulder Straps			
									75mm Lap Straps			
	Threaded Anchorages - Mark appropriate boxes to											

